



SUMP PUMPS & MORE



PUMP SELECTION GUIDE



64101

UTILITY PUMP 1/4 HP

- Thermoplastic construction resists corrosion
- 1-1/4" FPT outlet and includes 3/4" hose adapter
- 8' cord
- Pumps down to 1/8"

DISCHARGE HEIGHT IN GPH

0'	5'	10'	15'	20'
1320	1170	1020	810	510



64105

SUMP PUMP 1/4 HP

- TETHERED SWITCH
- Zinc housing for better heat dissipation and longer pump life
- 1-1/2" outlet
- Stainless steel hardware

DISCHARGE HEIGHT IN GPH

0'	5'	10'	15'	20'
3200	2700	2160	1500	-



64106

SUMP PUMP 1/3 HP

- TETHERED SWITCH
- Zinc housing for better heat dissipation and longer pump life
- 1-1/2" outlet
- Stainless steel hardware

DISCHARGE HEIGHT IN GPH

0'	5'	10'	15'	20'
3600	3060	2400	1680	660



64111

SUMP PUMP 1/3 HP

- VERTICAL SWITCH
- Zinc housing for better heat dissipation and longer pump life
- 1-1/2" outlet
- Stainless steel hardware

DISCHARGE HEIGHT IN GPH

0'	5'	10'	15'	20'
3600	3060	2400	1680	660



64112

SUMP PUMP 1/3 HP

- VERTICAL SWITCH
- CAST IRON BASE FOR LONGER LIFE
- Zinc housing for better heat dissipation and longer pump life
- 1-1/2" outlet
- Stainless steel hardware
- 2 year warranty

DISCHARGE HEIGHT IN GPH

0'	5'	10'	15'	20'
4200	3660	3000	2160	960



64117

SEWAGE PUMP 1/2 HP

- TETHERED SWITCH
- CAST IRON CONSTRUCTION FOR LONGER LIFE
- 2" outlet
- Stainless steel hardware
- 10' piggyback tethered switch for automatic or manual operation
- 3 year warranty

DISCHARGE HEIGHT IN GPH

0'	5'	10'	15'
9000	7320	5400	2700



64119

SEWAGE PUMP KIT 1/2 HP

- CAST IRON PUMP 64117 INCLUDED
- 18" x 30" basin
- 2" PVC pipe included and 2" check valve
- 2" outlet

DISCHARGE HEIGHT IN GPH

0'	5'	10'	15'
9000	7320	5400	2700